

## AutoDream Cam angle sensor setting

ECU Master :	primery
Sensor type	Optical/Hall
trigger type	Multitooth
trigger edge	falling
number of cylinders	6
Num teeth incl missing	12
first trigger tooth	10
trigger angle	57

**Note.** Under no circumstances you move the red wire from it's location  
Nissan uses a white wire for their 12v at the Cas on late modle Skylines and red green for trigger signals  
On Some ecu will require the green and Grey to swap their locations

- 1: Before you remove anything. Make sure you have a timing light and record your engine's base timing so you can set your new sensor trigger offset to match what your base timing was before you remove your stock sensor
- 2: remove stock CAS and set it aside you will need to reuse your 3 M6 bolts
- 3: remove the 4 M7 bolts holding your cam gear on your cam shaft
- 4: grind down the 8 corners on the stock washer plate slightly so it can fit inside the new rotor
- 5: install the rotor onto the front of your camgear by lining up the single hole with the dowe hole on your gear using your stock M7 bolts
- 6: install the sensor holder using your stock M6 bolts
- 7: install the sensor by turning the sensor in by hand until it bottom out then back it out 1/4 to 1/2 turn, then lock it in place using a 14mm wrench.( do not over tighten the nut
- 8: plug in the connector and zip tie to clear any moving parts
- 9: Start engine and check and adjust trigger offset to get your desire base timing.

Sensor wire funtions as follow

Black= Ground

Red= 12v

Grey= Crank signal which simulate 12 Cam or 24 Crank pulses per engine Revolution

Green= Cam Ref signal which is 1 pulse per engine revolution